



Surge Protector

NVS-021VPS-HD



| GENERAL | |
|--|--|
| Device Type | Power and Video 2 in 1 Surge Protector |
| VIDEO PROTECTION | |
| Continuous Operating Voltage | 5 V |
| Max Voltage Operating | 6 V |
| Nominal Discharging Current (8/20 μ s) | 5 kA |
| Max Discharging Current (8/20 μ s) | 10 kA |
| Limit Voltage (10/700 μ s) | < 20 V |
| Response Time | \leq 1ns |
| Insertion Impedence | \leq 1 Ω |
| Bandwidth | 100 MHz |
| POWER PROTECTION | |
| Continuous Operating Voltage | 24 V |
| Max Voltage Operating | 36 V |
| Nominal Discharging Current (8/20 μ s) | 5 kA |
| Max Discharging Current (8/20 μ s) | 10 kA |
| Limit Voltage | <200 V (8/20 μ s) |
| Rated Overload Current | \leq 10 A |
| Leakage Current | \leq 5 μ A |
| Response Time | \leq 25ns |
| INSTALLATION PARAMETERS | |
| Operating Temperature | -20°C ~ 55°C |
| Dimensions (mm) | 112 (W) x 63 (H) x 38 (L) |
| Case | aluminium, black |